



Sidewalks: (See section 10-116 of the Cameron City Code)

All sidewalks constructed, reconstructed, or modified in any manner shall be permanent Portland cement concrete and shall be natural concrete gray tone in color with a uniform, broom finish texture. No cobblestone, stamped or other irregular finish shall be permitted.

Minimum width is five (5) feet. Minimum thickness is four (4) inches for with a compacted aggregate base. Where vehicle traffic crosses walkway, the minimum thickness is six (6) inches reinforced with #4 rebar. All sidewalks shall be constructed to ADA specifications. Curb ramps are necessary where required (ADA 4.7).

Residential Driveways: (See section 7-347.1 of the Cameron City Code)

(Applies only to the portion within the right-of-way)

All driveways constructed, reconstructed, or modified in any manner shall be permanent Portland cement concrete and shall be natural concrete gray tone in color with a uniform, broom finish texture. No cobblestone, stamped or other irregular finish shall be permitted.

Minimum width is ten (10) feet; maximum width is thirty (30) feet. Minimum thickness is six (6) inches with a compacted aggregate base.

Driveways shall be well maintained to ensure that no damage to or deterioration of the public pavement is caused by the condition of a driveway.

Driveways and/or parking areas are required to accommodate two (2) parking spaces per dwelling unit and shall lead to a garage or side/rear parking area as per Zoning Article 24. The remainder of the driveway must be, at a minimum, an "all-weather" surface at least six (6) inches thick.

Mailboxes:

When installing a new mailbox or replacing an old one they must comply with USPS regulations using an approved traditional or contemporary mailbox. The front edge of the mailbox should be 6" to 8" behind the back of the curb.